KVT 80 | Split cable gland

for cables with connectors, suitable on cut-out M80 / IP54 / UL Type 12



UL TYPE **IP54**













The KVT 80 split cable glands are designed for routing and sealing cables with connectors. But also electric, pneumatic or hydraulic lines without terminals or connectors as well as corrugated conduits can be easily routed (e.g. into control panels, enclosures or machinery) and sealed with IP54 / UL Type 12.

By assembling the two frame halves with the screws provided, the grommets provide sufficient pressure on the routed cables to obtain a high degree of strain relief. By using <u>multi-hole grommets</u> up to 24 lines can be routed with one cable gland. The KVT 80 can be fitted to a wall thickness from 1.5 mm to 10 mm. A flat rubber gasket is included in the shipment.

When mounting the KVT 80 on sheet metal, we recommend the following torque values:

 $1.5 \text{ mm sheet} = 1 \text{ Nm} \mid 2 - 10 \text{ mm sheet} = 1.5 \text{ Nm}$


Specifications

IP rating (EN 60529)	IP54
Test UL Type (UL 50E)	UL Type 12
Material	Polycarbonate
Flame class	UL94-V0, self-extinguishing
Operating temperature	-30 C° to 100 C°
Properties	silicone free, halogen free
Mounting options	Screw type mounting

Advantages & Benefits

- Routing of cables with and without connectors
- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density, wide variety of grommets
- Fast and easy mounting from the front side
- Strain relief according to EN 62444

Product Types & Sizes




Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color External diameter

45237 4251269311376 1 24 17 mm gray (similar RAL 7035) 100 mm

Mounting height Cut-out size, metric Cut-out size, round Suitable for grommets


16 mm M80 80 mm 6 x KT small

KVT 80|6 bk



Part No. EAN Package quantity For max, no, of cables Max. cable diameter External diameter

Mounting height Cut-out size, metric Cut-out size, round Suitable for grommets 16 mm Mao 80 mm 6 x KT small



Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color

External diameter

9 35 mm


4251269311369

45236

1

gray (similar RAL 7035) 100 mm Mounting height Cut-out size, metric Cut-out size, round Suitable for grommets 16 mm M80 80 mm 2 x KT small 1 x KT large

KVT 80|3 bk



Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
External diameter

45239 4251269311390 1 9 35 mm black

100 mm

Mounting height Cut-out size, metric Cut-out size, round Suitable for grommets

16 mm M80 80 mm 2 x KT small 1 x KT large

