

KEL-DPR | 100 10000 1000 1000 10000

100 1000 10000 100 가 / IP65



IP54

ISO 4892-2A

IP55

RoHS compliant

IP64

REACH COMPLIANCE

IP65

HL3
EN 45545-2

ECOLAB
certified

KEL-DPR 24 1000 1000 10000 1000 KEL-DP 24. KEL-DPR 24 1000 1mm 16.1mm 100 48 1000 1000 1000 1000.

KEL-DPR 24 1000 1000 24 1000 1000 100 1000 10000. 100 1000 100 100 1000 10000. 1000 10000 100 ST-B 10000 10000.


M4 1000 1000 1000 1000 1000 1000 10000 1000 10000.

IP 10000 (EN 60529)	IP54, IP55, IP64, IP65
	100000 1000 1000000
	UL94-V0, 100000
	-40 C° to 90 C°
	100000, 1000 100
100 100	100 1000

100 1000

- 1000 1000000 100 1000 100
- 1000 1000 1000 100
- 100 100 100
- 100 100 100 100
- 100 100 10000 100
- 100000 M4 1000 1000 100 100 가

100 100 1000




EAN

1000 100
100 1000 100

46500
4251269335303
10
12
15 mm
147 mm

100 100
100 1000
100 100
1000 100
1000 100 100

58 mm
10,6 mm
9,1 mm
112 × 36 mm
4
5,8 mm
12 × 1 - 15 mm




EAN

1000 100
100 1000 100

46501
4251269335310
10
17
12,6 mm
147 mm

100 100
100 1000
100 100
1000 100
1000 100 100

58 mm
10,6 mm
9,1 mm
112 × 36 mm
4
5,8 mm
5 × 1 - 10.5 mm
12 × 1 - 12.6 mm




EAN

1000 100
100 1000 100

46502
4251269335327
10
25
12,1 mm
147 mm

100 100
100 1000
100 100
1000 100
1000 100 100

58 mm
10,6 mm
9,1 mm
112 × 36 mm
4
5,8 mm
18 × 1 - 6.5 mm
7 × 1 - 12.1 mm




EAN
□□□ □
□□ □□□ □□

46503
4251269335334
10
26
16,1 mm

147 mm

□□ □□
□□ □□□
□□ □ □
□□□ □□
□□□ □□ □

58 mm
10,6 mm
9,1 mm
112 × 36 mm
4
5,8 mm
16 x 1 - 6.5 mm
4 x 1 - 12.1 mm
4 x 1 - 16.1 mm



EAN
□□□ □
□□ □□□ □□

46504
4251269335341
10
48
6,5 mm

147 mm

□□ □□
□□ □□□
□□ □ □
□□□ □□
□□□ □□ □

58 mm
10,6 mm
9,1 mm
112 × 36 mm
4
5,8 mm
48 x 1 - 6.5 mm